



## Monitored Sliding Door Side Screen or Door Threshold Pedestrian Safety Sensor

Versatile and simple to set up, the HR94D1-C1 protects pedestrians from the dangers of both opening and closing sliding doors at mounting heights of up to 3m



- **Sliding Door Side Screen Pedestrian Safety**  
Protect pedestrians from the dangerous leading door edge during door open cycles with a dense curtain of infrared safety
- **Door Threshold Pedestrian Safety**  
Safeguard pedestrians from hazardous door closures due to a shallow but wide infrared safety curtain that is monitored once per door cycle
- **Solid & Reliable**  
Avoid the risk of loss or damage to individual sensor parts through a one piece sensor body construction
- **Simple to Install**  
Install with ease without the need for a remote control thanks to comprehensive instructions printed on the sensor body

# HR94D1-C1

Monitored Safety



## Technical Specification

Model	HR94D1-C1 Monitored Pedestrian Door Safety	
Detection Method	Active Infrared Detection	
Installation Height	Max 3000mm (10ft)	
Sensor Dimensions	210mm (W), 65mm (H), 30mm (D)	
Pattern Adjustment	Width Adjustment: Wide or Narrow (Dials) Depth Adjustment: Body Angle Adjustment 0° - 5° in 3 steps	
Presence Timer	2, 15, 60 & 180 seconds	
IP Rating	54	
Power Supply	12 to 32V AC or DC ± 10%	
Power Consumption	AC12V-1.8 [VA] (Max), DC12V-100 [mA] (Max) AC24V-2.8 [VA] (Max), DC24V-60 [mA] (Max)	
Output	Open Collector 7.5 [mA] (Max) Resistor Load	
Relay Hold Time	Approx. 0.5 sec	
LED Indication	Power On = Green ON Detecting = Red ON Detecting Door = Orange ON Self Diagnostics = Red/Green FLASHING	
Operating Temperature	-20°C to +60°C, (-4°F to 140°F)	
Weight	190g (0.42 lbs)	
Available Colours	Black: Product Code = HR94D1-C1/BL Silver: Product Code = HR94D1-C1/S	
Accessories Provided	2.5m Connection Cable Mounting Template Mounting Screws Installation Instructions	

### Accessories



1200R  
Spacer for installation  
on a round door



UTB-HR100  
Ceiling attached bracket



ITB-HR100  
Ceiling recessed bracket



Cable HR94D1-C1  
Hotron 2.5M Cable



HR94D-COV/S  
Silver sensor cover  
HR94D-COV/BL  
Black sensor cover



WC/BL  
Black weather cover

### Detection Area (inches/mm)

